

E-20 MODEL ANSI NO PRODUCT DESCRIPTIONS & FEATURES

E580EL **08**

- Storeroom Escutcheon Trim
- Turning Key Unlocks Lever To Withdraw Latchbolt
- Trim Locked When Power Applied
- Trim Unlocks When Power Removed (Fail Safe)
- Multi Voltage 12 or 24 VDC
- Escutcheon Plate Dimensions
9-7/16" x 2-15/26" x 13/16" (240mm x75mm x 21mm)
- Trim Requires Standard 1-1/4" Mortise Cylinder or IC Shell
- Trim Through Bolts Through The Device Head To Maintain Proper Alignment and For Greater Security



E580EU **08**

- Storeroom Escutcheon Trim
- Turning Key Unlocks Lever To Withdraw Latchbolt
- Trim Unlocks When Power Applied
- Trim Locks When Power Removed (Fail Secure)
- Multi Voltage 12 or 24 VDC
- Outside Lever Always Active (Freewheeling)
- Escutcheon Plate Dimensions
9-7/16" x 2-15/26" x 13/16" (240mm x75mm x 21mm)
- Trim Requires Standard 1-1/4" Mortise Cylinder or IC Shell
- Trim Through Bolts Through The Device Head To Maintain Proper Alignment and For Greater Security



Finishes : 630 Standard, 605, 606, 610. 613, 619, 625, 626 By Special Order

EPS1N

**Regulated 24VDC
Electrified Trim Power Supply**

Input voltage 120VAC
Output voltage 24 VDC regulated @ 1A
Temperature range - 0 to 120 F
Input 1 solid-state input
Output 1 solid-state output
LED - Red = power indicator
LED Green = Channel on
Dimensions - 10"(254)x 10"(254) x 4"(102)



Specifications

- UL Listed
- Solid-state electronic relay
- One dry inputs and one wet output
- Built In Fire Alarm Contacts
- Solid-state reverse polarity protection for battery connections