



**HOW TO ORDER STANDARD AND ELECTRIFIED MORTISE LOCKS** A-5

**Trim Information** (Rose and Escutcheon)

Type	Designation	Dimensions
Rose	A	Diameter 2-1/4" (57mm)
	B	Diameter 2-9/16" (65mm)
Escutcheon	E	Height 8-1/2" (216mm) Width 2" (51mm)
	G	Height 8-1/2" (203mm) Width 2-1/2" (64mm)

**NSO: Non Standard Options**

- Door Thickness Over 1-3/4"(44.5mm)
- Strike other than standard ANSI 4-7/8"
- Anti Microbial Coating
- Spanner Head Screws
- Tactile Warning
- Extra Large Thumbturn
- Spanner Head Screws

**How To Order Mortise Locks**



**NSO Non Standard Options:** Door Thickness, Strike Type and Accessibility Options. See Chart Above

**LBM** (Latch Bolt Monitoring)

- Latchbolt Monitoring Sends a Signal From a Form C Relay to An Access or Security System When The Latchbolt is Drawn Into The Head of The Lock Body By Either an Egress or an Entry From Outside By Trim or By Key.

**REX** (Request To Exit)

- Request To Exit Sends a Signal From a Form C Relay to An Access or Security System When an Authorized Exit is Made From The Egress Side Of The Opening, By Activating The Lever. This Function is Used to Shunt an Alarm.

**How To Order**

**Electrified Mortise Locks**

